


Type:
Project:
Comments:
Prepared By:

Part #	8194HRA				
Category #:	8194				
Product Category:	Recessed Fluorescent				
Description:	4" IC rated Airtight Compact fluorescent remodel housing				
Design Features					
Thermal Protection	Protected against misuse of insulation and improper wiring				
IC Rating	IC rated for direct contact w/ non cellulose type insulation				
Ј Вох	Listed for feed through wiring (4 in-4 out) and five ½" knockouts and four non metallic cable knockouts w/ strain clamps				
Wattage	1x13W & 1x18W				
Lamp	G24/GX24 socket				
Voltage	120V-60Hz				
Fit	Adjusts to fit up to 1" ceiling thickness. 6-3/8" height allows use in 2" x 8" joist construction.				
Warranty	1 year limited warranty				
Listing					
ETL/UL	cULus for damp location				
Meets Washington's State energy code for restricted airflow					











## **Trim Options**

	Туре	Item#	Finishes	O.D.
•	Baffle	8701	Black, white, oil rubbed bronze Optional BA, BK rings.	5"
	Shower Trim, Fresnel	8702FS	Wet location listed.	5"
	Reflector	8703	White, Clear, Brushed aluminum Optional BA, BK rings	5"
	Satin Glass	8704	Wet location listed White	5"
	Shower, Albalite	8705AL	Wet location listed	5"
9	Eyeball	8706	Brushed Aluminum, black, white	5"
	Wall Wash	8707WW	White	5"
	Satin Bubble Glass	8710	Wet location listed White	5"
•	Pin Hole	8721PN	White	5"
	Gimbal	8740	Black, white, brushed aluminum	5"
•	Baffle	8701	Black, white, oil rubbed bronze Optional BA, BK rings.	5"