
| б  |                 |
|----|-----------------|
| RP | LIGHTING • FANS |

| Туре:        |  |
|--------------|--|
| Project:     |  |
| Comments:    |  |
| Prepared By: |  |

| Part #               | 8195HRA  |  |  |  |
|----------------------|--|--|--|--|
| Category #:          | 8195   |  |  |  |
| Description:         | 5" IC rated Airtight Compact remodel fluorescent housing   |  |  |  |
| Design Features      |  |  |  |  |
| Thermal Protection   | Protected against misuse of insulation and improper wiring   |  |  |  |
| IC Rating            | IC rated for direct contact w/ non cellulose type insulation   |  |  |  |
| J Box                | Listed for feed through wiring (4 in-<br>4 out) and five ½" knockouts & four<br>non metallic cable knockouts w/<br>strain clamps   |  |  |  |
| Fit                  | Adjusts to fit up to 1" ceiling<br>thickness.<br>7-9/16" height allows use in 2" x 8"<br>joist construction.<br>Adjustable socket plate for proper<br>positioning of different lamp types. |  |  |  |
| Wattage              | 18W  |  |  |  |
| Lamp                 | G24/GX24   |  |  |  |
| Voltage              | 120V   |  |  |  |
| Warranty             | 1 year limited warranty  |  |  |  |
| Listing              |  |  |  |  |
| ETL/UL               | cULus for damp location  |  |  |  |
| Meets Washington's S | State energy code for restricted airflow   |  |  |  |











## **Trim Options**

| Туре      | ltem# | Finishes         | 0.D.   |
|-----------|-------|------------------|--------|
| Reflector | 8634  | Brushed Aluminum | 6 3/4" |