

8742

120V

Catalog #:		Type
Project:		Date
Prepared by:		

4" LED Wafer Light



4" LED Wafer Light

DESCRIPTION

The 8742 is a versatile LED down light solution. Edge-lit technology and an off-board driver allow for an ultra slim profile and flexible mounting options. Installation is a snap with the plenum-rated driver box and linkable connector cable - there is no need for a j-box or recessed housing. The simple spring-loaded retention tabs securely hold each downlight snug to the ceiling. Rated for use in wet locations the 8742 is perfect for use in tight plenums, hallways, bathrooms, basements, entry ways, porches, and many other areas around a home or multifamily development.

DESIGN FEATURES

Construction

- Ultra Slim profile
- Durable aluminum construction
- Frosted acrylic lens

Electrical

- 120V-60Hz
- Triac dimmable
- Suitable for use in wet locations
- 50,000 hour projected life
- 9W | 620Lm | 68.9Lm/W
- Available in 3000 or 4000K

Installation

- Simple installation with hinged, off-board driver/ junction box, poke-in connectors, and linkable connector cable.
- Spring-loaded retention tabs hold downlight snug to ceiling surface
- IC rated, suitable for direct contact with insulation

Lens

- Frosted acrylic lens diffuses glare and maximizes output
- 110° Beam angle

Finish

- Available in White *BN and OB finish special order

Certifications

- Energy Star
- c-ETL-us
- 5 year limited warranty

ORDERING

Example: 8742BN-3K

Model #	Finish		CCT
8742			
8742	WH	:	White -3K -4K



TEL: 800.937.6925 | Fax: 800.207.9509 | www.rplighting.com

Specifications and dimensions subject to change without notice.

