89xx Series

120V-60Hz

Catalog #:	Туре
Project:	
	Date
Prepared by:	

LED Under Cabinet Light



DESCRIPTION

The 89xx, 90 CRI series adds a touch of warmth and elegance to any cabinet/countertop application. Low-profile, energy efficient, and maintenance free with easy installation. Low-profile, easy installation, energy efficient and maintenance free.

DESIGN FEATURES

Construction

- Aluminum housing with Ribbed Acrylic Curved Lens
- Linkable design for hardwire and plug-in

Electrical

- 120V-60Hz
- Dimmable TRIAC, 10-100%
- 50,000 hour projected life
- 3000K | 90 CRI

Installation

- Hinged wiring trough for easy access to wires
- Fast hard-wiring with snap-in connector
- Each end-cap has one 3/4" knockout and capped linkable socket
- 8966/8967: (1) 1/2" knockout located on the back side of housing
- 8968-72: (2) 1/2" knockouts located on the back side of housing

Finish

Finish: white (WH) & brushed aluminum (BA)

Available Accessories

6" Connector cord: 897CN-6

12" Connector cord: 897CN-12

24" Power cord: 897PC-24

End-to-end connector: 897CN

Lens Replacement: 89xxL

Listing

- cCSAus Listed for damp location
- **CEC JA8 Compliant**
- LED Lamp: 5 Year Limited Warranty
- Other Components: 1 Year Limited Warranty

ORDERING	Example: 8966WH	
Model #	Finish	
8966: 9" 8967: 12" 8968: 18" 8969: 21" 8970: 24" 8971: 36" 8972: 48"	WH: White BA: Brushed Alumi	num











896 Series

120V-60Hz

Specification & Ordering

Model #	Size (LxDxH)	Lumens	Watts	CRI
8966	9" x 3-3/4" x 1-1/16"	Source 320lms, Delivered 250lms	4W	
8967	12" x 3-3/4" x 1-1/16"	Source 400lms, Delivered 315lms	5W	
8968	18" x 3-3/4" x 1-1/16"	Source 630lms, Delivered 500lms	7W	
8969	21" x 3-3/4" x 1-1/16"	Source 750lms, Delivered 595lms	8W	90
8970	24" x 3-3/4" x 1-1/16"	Source 850lms, Delivered 670lms	9W	
8971	36" x 3-3/4" x 1-1/16"	Source 1140lms, Delivered 900lms	13W	
8972	48" x 3-3/4" x 1-1/16"	Source 1500lms, Delivered 1190lms	17W	

TEL: 800.937.6925 | Fax: 800.207.9509 | www.rplighting.com

